



The power for your life

BW SERIES

600VA-3000VA



CPU controlled



Auto re-starts when AC recovers



Overload & short circuit protection



Automatic charging (offline charging)



Battery low voltage protection



Wide input voltage range



Silence setup

TECHNICAL PARAMETER

MODEL	BW-600VA/360W	BW-1200VA/720W	BW-1500VA/900W	BW-2000VA/1200W	BW-3000VA/1800W
Capacity	600VA/360W	1200VA/720W	1500VA/900W	2000VA/1200W	3000VA/1800W
INPUT					
Input voltage	220/230/240Vac				
Input voltage range	145-290Vac		175-275Vac		
Frequency range	45-65Hz				
OUTPUT					
Output voltage	220/230/240Vac				
Output voltage range	200-255Vac		198-242Vac		
Output frequency	60 ± 0.5Hz or 50 ± 0.5Hz (Auto sensing)				
Output wave form	PWM (Batt. mode)				
Transfer time	3ms				
BATTERY					
QTY. & capacity of battery	12V/7AH × 1pc	12V/7AH × 2pcs	12V/9AH × 2pcs	12V/9AH × 2pcs	12V9AH × 4pcs
Charging period	4-6 hours recover to 90% capacity				
PROTECTION					
Full protection	Low voltage & overload & short circuit protection				
PHYSICAL					
Unit dimension (mm)	275*95*140	330 * 122 * 192		345 * 122 * 192	412 * 145 * 210
Net weight (kg)	4.2	8.5	10.1	10.8	20
ENVIRONMENT					
Environment of performance	Temperature 0°C-40°C, Humidity 20%-90%				
Noise level	≤40dB(1m)				
MANAGEMENT					
LCD, RJ45 & USB	Standard				

Product specifications are subject to change without notice.

ADD: BURG KNAPPERTLAAN 247B, 3116JG SCHIEDAM, NETHERLANDS.
EMAIL: INFO@ULTRA-ON.COM S://WWW.WWW.ULTRA-ON.COM
VERSION NO.: B-20240001



@2024 ultra. All rights reserved.