

Product datasheet

Specifications



APC Easy UPS On-Line, 6kVA/6kW, Tower, 230V, Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, LCD, Extended Runtime

SRV6KIL

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
--------------	---

Main

Main input voltage	230 V AC 1 phase
Other input voltage	220 V 240 V
Efficiency at full load	110...300 V 60 % load 176...300 V full load
Input connection	1 hard wire 3-wire (1P + N + E)
Input frequency	40...70 Hz auto sensing
Output voltage	230 V AC 1 phase
Other output voltage	220 V 240 V
Rated power in W	6000 W
Rated power in VA	6000 VA
Output connection	Hard wire 3-wire (1P + N + E) for 1 zone(s)
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	1 %
Maximum configurable power in VA	6000 VA
Maximum configurable power in W	6000 W
UPS topology	On-Line
Waveform type	Sine wave
Efficiency	94 % (full load)
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery type	Lead-acid external included

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slot	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	Serial port USB port Available expansion slot
Surge energy rating	600 J
Color	Black (RAL 7010)
Height	368 mm
Width	380 mm
Depth	485 mm
Product weight	73 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
USB compatible	Yes
Mounting position	Vertical
Mounting mode	Tower
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Easy UPS On-Line
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	CE UKCA EAC TISI
Standard	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...60 °C
Storage altitude	0...15000 m
IP protection	IP20
Relative humidity	0...95 % non-condensing
Storage relative humidity	0...95 % non-condensing
Acoustic level	55 dBA
Heat dissipation	1172 Btu/h
Operating altitude	0...3000 m

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	240 V
Extendable runtime	1
Included battery module	0
Empty battery slot	0
Typical recharge time	5 h
Battery life	3...5 year(s)
Battery charging power	1170 W rated
Battery power in VAh	1512 VAh runtime

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	46 cm
Package 1 Width	57 cm
Package 1 Length	58 cm
Package 1 Weight	79 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	726 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	364 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	24 kg CO2 eq.
Carbon footprint of the installation phase [A5]	28 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	276 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	34 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	409c68a1-39a6-4e5f-b080-12befe783ad8
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	48
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



